

## YL-300B Automatic Pillow Packing Machine

### Instruction:

This machine is suitable for packing slice biscuit, chocolate, ice cream, card, bread and so on.



### Main Technical Parameters

Max. Production Capacity	30-140 bags/min	80-290bags/min	80-350bags/min
Packaging Range	Length	170-400mm	80-300mm
	Width	35-100mm	35-100mm
	Height	<75mm	<40mm
Max. Dia of Film		Φ350mm	60-100mm
Max Width of Film		300mm	35-100mm
Gross Power		3 Kw	
Power Supply		220V 50Hz	
Gross Weight		900kg	
Overall Dimension		4200×850×1550mm	

Notes:if any change of data,we will not notify further.


## YL-3520 Corner Labeling Machine



### Main Technical Parameters

Packing Speed	80-850packs/min
Packing size	L85-300mm, W30-100mm, H 5-30mm
Accuracy	±1mm
Container range	Max.260×80×76mm
Label range	Round label max diameter 50mm
Label roll	Max Φ350mm Paper roller Φ 76mm
Label and body paper distance	2mm
Standard power supply	220V/50Hz
Total power	1.75kw
Label body paper	62g/m <sup>2</sup> Thickness 55μm±5 Glassine
Tensile strength	Lengthways 16kg/25mm; Breadth 7kg/25mm
Rearing strength	Lengthways 25g/pcs; Breadth 31g/pcs
Transparency	52%
Labels distance	3-4mm ±0.2mm
Dimensions (L×W×H)	2400×1350×1500mm
Weight	750 kg

Notes:if any change of data,we will not notify further.



## YL-50/80 Automatic Tube Filling and Sealing Machine(plastic or aluminum)

### Instruction:

This machine is suitable for operating filling, sealing a quantity of viscosity of oil, cream and gel ointment



### Main Technical Parameters

Model	YL-50	YL-80
Filling volume	5-250ml (plastic/aluminum tube) it can adjust	5-250ml (plastic/aluminum tube) it can adjust
Filling accuracy	≤ ±0.5%	≤ ±0.5%
Capacity	30-50(tubes/min Adjustable)	60-80(tubes/min Adjustable)
Tube diameter	φ10- 60mm	φ10- 60mm
Tube length	200mm (Max. Length)	200mm (Max. Length)
Hopper volume	40 L	40 L
Power	380v/50hz	380v/50hz
Compressed Air	0.55-0.65MPa	0.5-0.65MPa
Equipped motor	1.5Kw	1.5Kw
Heat sealing power	3.3Kw	3.3Kw
Dimension	2000 × 1200 × 2000mm (L × W × H)	2424 × 1000 × 2020mm (L × W × H)
Weight	950kg	1500kg

Notes:If any change of data,we will not notify further.

## YL-200D Automatic Rotary Bag-Given Packing Machine

### Instruction:

YL-200D Automatic intermittent rotary preformed bags dispensing, opening and closing, machine combined with automatic Multi-heads Combination Weigh Scale Filler, Overhead Work Platform and Z-elevator bluk feeder.



### Working Process

- 1 Giving bag
- ↓
- 2 Coding date(option)
- ↓
- 3 Open zipper
- ↓
- 4 Open the top and bottom
- ↓
- 5 Filling, vibrate(option)
- ↓
- 6 Reserve
- ↓
- 7 Exhaust(option), closing zipper, sealing
- ↓
- 8 Forming and output



### Main Technical Parameters

No.of working station	Eight-working Station
Bag type	All type of heat sealable preformed side seal bags, fin seal bags, gusseted bags, block bottom bags, zip-lock recloseable bags, stand-up pouch with or without spout etc.
Bag size	W:80-220mm L:100-300mm
Filling volume	10-1500g
Capacity	25-60bags/min depend on type of product and packaging materials used
Accuracy	Error ≤ ±1%
Total power consumption	5KW
Application	Candy, biscuit, peanut, cookies, pistachio, crystal candy, brown sugar, daily commodities, cooked food, pickles, puffed food etc.
Optional equipment	Dosing assembly, materials bulk feed system, special down stream attachments etc.

Notes:If any change of data,we will not notify further.