YL-450 Intermittent Automatic Cartoning Machine For Aluminum Foil

Instruction:

Automatic Cartoning Machine can suitable for aluminum foil, preservative film, cling film, plastic wrapper into carton. Machine finished running by a series of photo-electro controller to make the machine stability and guarantee the packing quality. It includes cantons opening and forming, products insert into carton, printing batch number, sealing by tuck-in or hot-glue device. The machine can be single used or linked with VFFS Machine, Shrink Machine, Overwrapping Machine and pillow packing machine to form a production line.

Feature:

- 1.International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- Adopt human-machine operation system.
- 3. Automatically displaying device for trouble, speed and finished products counting.
- 4.Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons
- 5.No products no suction carton. Automatic detection and rejection device for lacking product.

Main Technical Parameters

Encasing Speed		20-30 Boxes/min
Carton	Quality requirement	250-450g/m ²
	Dimension range (L \times W \times H)	(100-450) × (20-80) × (20-90)mm
Compressed Air	Working pressure	≥0.6Mpa
	Air consumption	20m³/h
Motor power		380V/50Hz 1.5kw
Machine dimension (L × W × H)		4200 × 1700 × 1700mm
Machine weight		1600kg



Notes:If any change of data, we will not notify further.



YL-450B Automatic Continuously Cartoning Machine For Aluminum Foil

Instruction:

Automatic Cartoning Machine can suitable for aluminum foil, preservative film, cling film, plastic wrapper into carton. Machine finished running by a series of photo-electro controller to make the machine stability and guarantee the packing quality. It includes cantons opening and forming, products insert into carton, printing batch number, sealing by tuck-in or hot-glue device. The machine can be single used or linked with VFFS Machine, Shrink Machine, Overwrapping Machine and pillow packing machine to form a production line.



Feature:

- 1.International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- 2.Adopt human-machine operation system.
- 3. Automatically displaying device for trouble, speed and finished products counting.
- 4.Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons
- 5.No products no suction carton. Automatic detection and rejection device for lacking product.

Main Technical Parameters

Encasing Speed		40-90boxes/min	
Carton	Quality requirement	300-450g/m ²	
	Dimension range (L × W × H)	(100-480)×(25-80)×(25-55)mm	
Compressed	Working pressure	≥0.6mpa	
Air	Air consumption	140-180L/min	
Power		380V/50Hz	
Motor power		2.2kw	
Machine dimension (L × W × H)		4400×2500×1800mm	
Machine weight		2000kg	

Notes:If any change of data, we will not notify further.

16. | www.yilemachine.com |