YL-50/80 Automatic Tube Filling and Sealing Machine(plastic or aluminum)

Instruction:

This machine is suitable for operating filling, sealing a quantity of viscosity of oil, cream and gel ointment







Main Technical Parameters

Model	YL-50	YL-80
Filling volume	5-250ml (plastic/aluminum tube) it can adjust	5-250ml (plastic/aluminum tube) it can adjust
Filling accuracy	≤±0.5%	≤±0.5%
Capacity	30-50(tubes/min Adjustable)	60-80(tubes/min Adjustable)
Tube diameter	ф 10- 60mm	ф 10- 60mm
Tube length	200mm (Max. Length)	200mm (Max. Length)
Hopper volume	40 L	40 L
Power	380v/50hz	380v/50hz
Compressed Air	0.55-0.65MPa	0.5-0.65MPa
Equipped motor	1.5Kw	1.5Kw
Heat sealing power	3.3Kw	3.3Kw
Dimension	2000 × 1200 × 2000mm (L × W × H)	2424 × 1000 × 2020mm (L × W × H)
Weight	950kg	1500kg

YL-200D Automatic Rotary Bag-Given Packing Machine

Instruction:

YL-200D Automatic intermittent rotary preformed bags dispending, opening and closing, machine combined with automatic Multi-heads Combination Weigh Scale Filler, Overhead Work Platform and Z-elevator bluk feeder.





Working Process





Main Technical Parameters

No.of working station	Eight-working Station	
Bag type	All type of heat sealable preformed side seal bags, fin seal bags, gusseted bags, block bottom bags,	
	zip-lock recloseable bags, stand-up pouch with or without spout etc.	
Bag size	W:80-220mm L:100-300mm	
Filling volume	10-1500g	
Capacity	25-60bags/min depend on type of product and packaging materials used	
Accuracy	Error ≤ ±1%	
Total power consumption	5KW	
Application	Candy, biscuit, peanut, cookies, pistachio, crystal candy, brown sugar, daily commodities, cooked food,	
	pickles, puffed food etc.	
Optional equipment	Dosing assembly, materials bulk feed system, special down stream attachments etc.	

Notes:If any change of data, we will not notify further.

33. | www.yilemachine.com |