

YL-60 Automatic Cartoning Machine

Instruction:

Automatic Cartoning Machine can suitable for food product into carton, such as cake, biscuit, milk pouch, chocolate bar, coffee sachet, sticks, food sachet/pouch, ice cream/popsicle, cheese, frozen product, chicken, can, food tray, pillow pack product ,film roller, tissue, bulb ,bearing, pencil, protective pad ,mask ,other product .The machine finished running by a series of photo-electro controller to make the machine stability and guarantee the packing quality. It includes cantons opening and forming, products insert into carton, printing batch number, sealing by tuck-in or hot-glue device. The machine can be single used or linked with VFFS Machine, Shrink Machine, Overwrapping Machine and pillow packing machine to form a production line.



Feature:

- 1.International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- 2.Adopt human-machine operation system.
- 3.Automatically displaying device for trouble, speed and finished products counting.
- 4.Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons .
- 5.No products no suction carton, Automatic detection and rejection device for lacking product.

Main Technical Parameters

Encasing speed	30-60 Boxes/min	
Carton	Quality requirement	250-350g/m ²
	Dimension range (L × W × H)	(70-250) × (80-180) × (20-90)mm
Compressed Air	Working pressure	≥0.6Mpa
	Air consumption	20m ³ /h
Motor power	380V/50Hz 1.5kw	
Machine dimension (L × W × H)	3800 × 1350 × 1900mm	
Machine weight	1600kg	

Notes:If any change of data,we will not notify further.



YL-40 Automatic Cartoning Machine

Instruction:

Automatic Cartoning Machine can suitable for food product into carton, such as cake, biscuit, milk pouch, chocolate bar, coffee sachet, sticks, food sachet/pouch, ice cream/popsicle, cheese, frozen product, chicken, can, food tray, pillow pack product ,film roller, tissue, bulb ,bearing, pencil, protective pad ,mask ,other product .The machine finished running by a series of photo-electro controller to make the machine stability and guarantee the packing quality. It includes cantons opening and forming, products insert into carton, printing batch number, sealing by tuck-in or hot-glue device. The machine can be single used or linked with VFFS Machine, Shrink Machine, Overwrapping Machine and pillow packing machine to form a production line.

Feature:

- 1.International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- 2.Adopt human-machine operation system.
- 3.Automatically displaying device for trouble, speed and finished products counting.
- 4.Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons
- 5.No products no suction carton, Automatic detection and rejection device for lacking product.

Main Technical Parameters

Encasing speed	30-40 Boxes/min	
Carton	Quality requirement	250-350g/m ²
	Dimension range (L × W × H)	(70-350) × (80-200) × (20-90)mm
Compressed Air	Working pressure	≥0.6Mpa
	Air consumption	20m ³ /h
Motor power	380V/50Hz 1.5kw	
Machine dimension (L × W × H)	4000 × 1350 × 1900mm	
Machine weight	1600kg	

Notes:If any change of data,we will not notify further.

